

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



NAUTILUS FAST EPOXY LIGHT FILLER comp. B - Safety Data Sheet may 2016 n°614001 rev.1/16

NAUTILUS FAST EPOXY LIGHT FILLER comp. B

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Product name **NAUTILUS EPOXY FAST LIGHT FILLER comp. B**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Filler for industrial or professional application. For information regarding additional possible application please email us or dial the indicated phone number as shown below. We will connect you with our responsible technical personnel.

1.3. Details of the supplier of the safety data sheet

Company name: CECCHI GUSTAVO & C. SRL.
Via M.Coppino, 253
55049 VIAREGGIO(LU) ITALY
TEL. +39 0584 383694 FAX +39 0584 395182 info@cecchi.it

1.4 Emergency telephone number:

+39 0584/383694 From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30 - info@cecchi.it

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Acute Tox. 4: H302; Muta. 2: H341; Skin Corr. 1B: H314; Skin Sens. 1: H317

Most important adverse effects: Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects.

2.2. Label elements

Label elements:

Hazard statements:

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H341: Suspected of causing genetic defects.

Signal words: Danger

Hazard pictograms:



Precautionary statements:

P102: Keep out of reach of children.

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+312: IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+313: If skin irritation or rash occurs: Get medical.

P363: Wash contaminated clothing before reuse.

P405: Store locked up.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

	EINECS	CAS	PBT / WEL	Classificazione (CLP)	Percento
HEXAMETHYLEN-1,6-DIISOCYANAT HOMOPOLYMER	-	28182-81-2	-	Skin Sens. 1: H317	30-50%
M-XYLYLENDIAMIN	-	1477-55-0	-	Acute Tox. 4: H302+332; Aquatic Chronic 3: H412; Skin Corr. 1B: H314; Skin Sens. 1: H317	1-10%
BENZYL ALCOHOL	202-859-9	100-51-6	-	Muta. 2: H341; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Skin Corr. 1B: H314	1-10%
POLYOXYPROPYLENEDIAMINE	9046-10-0			Skin Corr. 1B: H314	1-10%
PHENOL	203-632-7	108-95-2		Muta. 2: H341; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Skin Corr. 1B: H314	1-10%
LOW BOILING POINT NAPHTHA - SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPH.	265-192-2	64742-89-8		Asp. Tox. 1: H304; Flam. Liq. 1: H224; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	1-10%
N-OCTYLAMIN		111-86-4		Acute Tox. 4: H302+312+332; Skin Corr. 1A: H314; Aquatic Acute 1: H400	<1%

Section 4: First aid measures**4.1. Description of first aid measures**

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.



Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Coated steel.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PHENOL

Workplace exposure limits:

Respirable dust

	TWA 8 ore	STEL 15 min	TWA 8 ore	STEL 15 min
IT	7.8 mg/m ³	-	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. In case of potential overshooting of the occupational exposure limit values or when damaging

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



NAUTILUS FAST EPOXY LIGHT FILLER comp. B - Safety Data Sheet may 2016 n°614001 rev.1/16

effects such as respiratory tract irritations occur a respiratory protection should be worn.
Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Chemical resistant gloves classified under DIN EN 374 have to be worn. Material of these gloves: butyl rubber, nitrile rubber, PVC or vinyl. For longer or repeated contact a glove with protection index 6 is recommended (breakthrough time >480 minutes according to DIN EN 374). For a short contact a glove with protection index 1 or higher is recommended (breakthrough time > 10 minutes according to DIN EN 374).

Eye protection: Wear goggles (with side protection). Goggles (with side protection) should be in compliance with the requirements of EN 166 or similar. Provide eye shower. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Environmental: Ensure all engineering measures mentioned in section 7 of SDS are in place.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Liquid
Colour:	Grey
Solubility in water:	Not miscible
Also soluble in:	Most organic solvents.
Viscosity:	Non-viscous
Boiling point/range°C:	n.V.
Melting point/range°C:	n.V.
Flammability limits %: lower:	n.V.
upper:	n.V.
Flash point°C:	100
Part.coeff. n-octanol/water:	n.V.
Autoflammability°C:	n.a.
Vapour pressure:	n.V.
Relative density:	0,5-0,7 g/cm ³
pH:	n.a.
VOC g/l:	76

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BENZYL ALCOHOL

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360	mg/kg
ORL	RAT	LD50	1230	mg/kg

PHENOL

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



NAUTILUS FAST EPOXY LIGHT FILLER comp. B - Safety Data Sheet may 2016 n°614001 rev.1/16

ORL	MUS	LD50	270	mg/kg
ORL	RAT	LD50	317	mg/kg
SCU	RAT	LD50	460	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations:

Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 04 09

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1759

14.2. UN proper shipping name

Shipping name: CORROSIVE SOLID,
(M-XYLYLENDIAMIN; POLYOXYPROPYLENEDIAMINE; PHENOL)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Tunnel code: E

Transport category: 2

CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY
tel. +39 0584 383694 fax +39 0584 395182
www.cecchi.it info@cecchi.it



NAUTILUS FAST EPOXY LIGHT FILLER comp. B - Safety Data Sheet may 2016 n°614001 rev.1/16

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

Phrases used in s.2 and s.3: H224: Extremely flammable liquid and vapour.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H302+312+332: Harmful if swallowed, in contact with skin or if inhaled.

H302+332: Harmful if swallowed or if inhaled.

H304: May be fatal if swallowed and enters airways.

H311: Toxic in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H341: Suspected of causing genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legend to abbreviations:

PNEC = predicted no effect concentration

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

OPT = optical

INH = inhalation

PCP = physico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.