

## C-SYSTEMS 10 10 UV PROTECTION component B

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Trade name: **C-SYSTEMS 10 10 UV PROTECTION component B**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture: Epoxy Hardener

#### 1.3 Details of the supplier of the safety data sheet

Company Cecchi Gustavo & C. srl - Via M. Coppino 253,  
55049 Viareggio (LU) ITALY www.cecchi.it - info@cecchi.it

Information in case of emergency: +39 0584 383694 - info@cecchi.it

From monday to friday office hours 8:30 – 12:30, 14:00 – 18:30

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4	H302: Harmful if swallowed.
Skin corrosion, Category 1B	H314: Causes severe skin burns and eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Chronic aquatic toxicity, Category 3	H412: Harmful to aquatic life with long lasting effects.

##### Classification (67/548/EEC, 1999/45/EC)

Corrosive	R34: Causes burns.
Harmful	R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
Sensitising	R43: May cause sensitisation by skin contact.
Dangerous for the environment	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/eye protection/ face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Takeoff immediately all contaminated clothing. Rinse skin with water/ shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/ physician.

Hazardous components which must be listed on the label: benzyl alcohol

octahydro-4,7-methano-1H-indenedimethylamine

3-aminomethyl-3,5,5-trimethylcyclohexylamine

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane,

reaction products with trimethylhexane-1,6

trimethylhexane-1,6-diamine

#### 2.3 Other hazards

**CECCHI GUSTAVO & C.**

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
 tel. +39 0584 383694 fax +39 0584 395182  
 www.cecchi.it info@cecchi.it



**C-SYSTEMS 10 10 UV PROTECTION comp. B** - SAFETY DATA SHEET - november 2015- n° batch 274-AE rev.4/15

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures**

Chemical nature : Cycloaliphatic amine based mixture

**Hazardous components**

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
benzyl alcohol	100-51-6 202-859-9 01- 2119492630-38	Xn; R20/22	Acute Tox. 4; H332 Acute Tox. 4; H302	>= 30 - < 50
octahydro-4,7- methano- 1Hindenedimethylamine	68889-71-4 272-573-7	Xn; R21/22 C; R34 Xi; R43	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Skin Sens. 1; H317	>= 30 - < 50
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8 01- 2119514687-32	C; R34 Xn; R21/22 R43 R52-R53	Acute Tox. 4; H312 Acute Tox. 4; H302 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 12,5 - < 20
4,4'- Isopropylidenediphenol, oligomeric reaction products with 1-chloro- 2,3-epoxypropane, reaction products with trimethylhexane-1,6	153195-44-9	Xn; R22 C; R34 R43 R52/53	Acute Tox. 4; H302 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 7 - < 10
Poly[oxy(methyl-1,2- ethanediyl)], .alpha.-(2- aminomethylethyl)- .omega.-(2- aminomethylethoxy)-	9046-10-0	C; R34 Xi; R41 R52/53	Skin Corr. 1C; H314 Eye Dam. 1; H318 Aquatic Chronic 2; H411	>= 3 - < 5
trimethylhexane-1,6- diamine	25620-58-0 247-134-8	Xn; R22 C; R34 Xi; R43 N; R52/53	Acute Tox. 4; H302 Skin Corr. 1B; H314 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 0,5 - < 1

For explanation of abbreviations see section 16

**SECTION 4: First aid measures**

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. B - SAFETY DATA SHEET - november 2015- n° batch 274-AE rev.4/15

### 4.1 Description of first aid measures

General advice : Show this safety data sheet to the doctor in attendance.

Keep warm and in a quiet place.

Take off all contaminated clothing immediately.

If inhaled : Move to fresh air.

Keep patient warm and at rest.

If unconscious place in recovery position and seek medical advice.

If symptoms persist, call a physician.

If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Wash off immediately with soap and plenty of water.

Do NOT use solvents or thinners.

If on clothes, remove clothes.

Burns must be treated by a physician.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

If eye irritation persists, consult a specialist.

If easy to do, remove contact lens, if worn.

If swallowed : Do NOT induce vomiting.

If a person vomits when lying on his back, place him in the recovery position.

Call a physician immediately.

Give small amounts of water to drink.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : corrosive effects

Burn

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No information available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)

Foam

Dry powder

Water mist

Unsuitable extinguishing media

: None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : The pressure in sealed containers can increase under the influence of heat.

Cool closed containers exposed to fire with water spray.

Hazardous decomposition products formed under fire conditions.

### 5.3 Advice for firefighters

Special protective equipment for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Further information : In the event of fire and/or explosion do not breathe fumes.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Immediately evacuate personnel to safe areas.

Prevent fire extinguishing water from contaminating surface water or the ground water system.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.

Evacuate personnel to safe areas.

Use personal protective equipment.

Ensure adequate ventilation.

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. B - SAFETY DATA SHEET - november 2015- n° batch 274-AE rev.4/15

Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

### 6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.

Try to prevent the material from entering drains or water courses.

Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Pick up and transfer to properly labelled containers.

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours or spray mist.

Avoid inhalation, ingestion and contact with skin and eyes.

Wear personal protective equipment.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition. Hygiene measures : Provide adequate ventilation. Wash hands and face before breaks and immediately after handling the product.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep containers tightly closed in a dry, cool and well ventilated place. Keep in properly labelled containers. To maintain product quality, do not store in heat or direct sunlight.

Further information on storage conditions : Protect from moisture.

Advice on common storage : Keep away from isocyanates.

Do not store near acids.

Keep away from oxidizing agents.

Other data : Stable at normal ambient temperature and pressure.

### 7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**

benzyl alcohol : End Use: Workers

Exposure routes: Inhalation

Potential health effects: Short-term exposure, Systemic effects

Value: 450 mg/m<sup>3</sup>

End Use: Workers

Exposure routes: Inhalation

Potential health effects: Long-term exposure, Systemic effects

Value: 90 mg/m<sup>3</sup>

End Use: Workers

Exposure routes: Skin contact

Potential health effects: Short-term exposure, Systemic effects

Value: 47 mg/kg

End Use: Workers

Exposure routes: Skin contact

Potential health effects: Long-term exposure, Systemic effects

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



**C-SYSTEMS 10 10 UV PROTECTION comp. B** - SAFETY DATA SHEET - november 2015- n° batch 274-AE rev.4/15

Value: 9,5 mg/kg  
End Use: Consumers  
Exposure routes: Ingestion  
Potential health effects: Short-term exposure, Systemic effects  
Value: 25 mg/kg  
End Use: Consumers  
Exposure routes: Ingestion  
Potential health effects: Long-term exposure, Systemic effects  
Value: 5 mg/kg  
End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: Short-term exposure, Systemic effects  
Value: 40,55 mg/m<sup>3</sup>  
End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: Long-term exposure, Systemic effects  
Value: 8,11 mg/m<sup>3</sup>  
End Use: Consumers  
Exposure routes: Skin contact  
Potential health effects: Short-term exposure, Systemic effects  
Value: 28,5 mg/kg  
End Use: Consumers  
Exposure routes: Skin contact  
Potential health effects: Long-term exposure, Systemic effects  
Value: 5,7 mg/kg

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-  
: End Use: Workers  
Exposure routes: Skin contact  
Potential health effects: Long-term systemic effects  
Value: 2,5 mg/kg  
End Use: Workers  
Exposure routes: Skin contact  
Potential health effects: Long-term local effects  
Value: 0,623 mg/cm<sup>2</sup>  
End Use: Consumers  
Exposure routes: Skin contact  
Potential health effects: Long-term systemic effects  
Value: 1,25 mg/kg  
End Use: Consumers  
Exposure routes: Skin contact  
Potential health effects: Long-term local effects  
Value: 0,311 mg/cm<sup>2</sup>  
End Use: Consumers  
Exposure routes: Ingestion  
Potential health effects: Long-term systemic effects  
Value: 0,04 mg/kg

### **Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

benzyl alcohol : Fresh water  
Value: 1 mg/l

Marine water  
Value: 0,1 mg/l  
Fresh water sediment

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. B - SAFETY DATA SHEET - november 2015- n° batch 274-AE rev.4/15

Value: 5,27 mg/kg  
Marine sediment  
Value: 0,527 mg/kg  
Soil  
Value: 0,456 mg/kg  
Sewage treatment plant  
Value: 39 mg/l  
Intermittent releases  
Value: 2,3 mg/l

3-aminomethyl-3,5,5-trimethylcyclohexylamine

: Fresh water  
Value: 0,06 mg/l  
Marine water  
Value: 0,006 mg/l  
Intermittent releases  
Value: 0,23 mg/l  
Fresh water sediment  
Value: 5,784 mg/kg  
Marine sediment  
Value: 0,578 mg/kg  
Sewage treatment plant  
Value: 3,18 mg/l  
Soil  
Value: 1,121 mg/kg

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-

: Fresh water  
Value: 0,015 mg/l  
Marine water  
Value: 0,0143 mg/l  
Fresh water sediment  
Value: 0,132 mg/kg  
Marine sediment  
Value: 0,125 mg/kg  
Soil  
Value: 0,0176 mg/kg  
Intermittent releases  
Value: 0,15 mg/l  
Sewage treatment plant  
Value: 7,5 mg/l

### 8.2 Exposure controls

#### Engineering measures

Effective exhaust ventilation system  
effective ventilation in all processing areas

#### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Do not wear contact lenses.

Ensure that eyewash stations and safety showers are close to the workstation location.

Hand protection

Material : Chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374.

Skin and body protection : Protective suit

Respiratory protection : Use respirator when performing operations involving potential exposure to vapour of the product.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. B - SAFETY DATA SHEET - november 2015- n° batch 274-AE rev.4/15

exceeded, selfcontained breathing apparatus must be used. Respirator with a vapour filter (EN 141)  
Protective measures : Avoid contact with skin. Wear suitable protective equipment.

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance :	liquid
Colour :	light yellow
Odour :	ammoniacal
Odour Threshold :	not determined
pH :	not determined
Melting point/freezing point :	Not applicable
Boiling point/boiling range :	> 200 °C
Flash point :	100 °C
Evaporation rate :	not determined
Upper explosion limit :	Not applicable
Lower explosion limit :	Not applicable
Vapour pressure :	Not applicable
Relative vapour density :	not determined
Density :	1,01 g/cm <sup>3</sup> (25 °C)
Bulk density :	not determined
Solubility(ies)	
Solubility in other solvents :	not determined
Partition coefficient: noctanol/water:	No data available
Auto-ignition temperature :	Not applicable
Thermal decomposition : Method:	No data available
Viscosity	
Viscosity, dynamic :	60 - 120 mPa.s (25 °C)
Viscosity, kinematic :	not determined
Explosive properties :	Not applicable
Oxidizing properties :	Not applicable

#### 9.2 Other information

Surface tension : not determined  
Sublimation point : Not applicable

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Stable under recommended storage conditions.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with the following substances:

Acids

Strong oxidizing agents

#### 10.4 Conditions to avoid

Conditions to avoid : No decomposition if used as directed.

#### 10.5 Incompatible materials

Materials to avoid : Strong acids

Strong oxidizing agents

#### 10.6 Hazardous decomposition products

Hazardous decomposition products: This product may release the following:

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide

Carbon dioxide (CO<sub>2</sub>)

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects



## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. B - SAFETY DATA SHEET - november 2015- n° batch 274-AE rev.4/15

### Acute toxicity

#### Product:

Acute oral toxicity : Acute toxicity estimate : 529,32 mg/kg

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 2.000 mg/kg

Method: Calculation method

### Components:

#### benzyl alcohol:

Acute inhalation toxicity : LC50 (Rat, male and female): > 4.178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: yes

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : Acute toxicity estimate : 500 mg/kg

Method: Converted acute toxicity point estimate

Acute dermal toxicity : Acute toxicity estimate : 1.100 mg/kg

Method: Converted acute toxicity point estimate

#### Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-:

Acute oral toxicity : LD50 (Rat, male and female): 2.885,3 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute dermal toxicity : LD50 (Rabbit, male and female): 2.979,7 mg/kg

Method: OECD Test Guideline 402

GLP: yes

### Skin corrosion/irritation

#### Product:

Remarks: Acute dermal irritation/corrosion

#### Components:

##### benzyl alcohol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: yes

##### Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Corrosive

### Serious eye damage/eye irritation

#### Product:

Remarks: Severe eye irritation

#### Components:

##### benzyl alcohol:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Eye irritation

GLP: yes

##### Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-:

Method: OECD Test Guideline 405

Result: Risk of serious damage to eyes.

### Respiratory or skin sensitisation

#### Product:

Remarks: No data available



## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. B - SAFETY DATA SHEET - november 2015- n° batch 274-AE rev.4/15

### Germ cell mutagenicity

#### Carcinogenicity

#### Reproductive toxicity

#### STOT - single exposure

#### STOT - repeated exposure

#### Repeated dose toxicity

#### Product:

Remarks: No data available

#### Aspiration toxicity

#### Components:

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

No aspiration toxicity classification

#### Further information

#### Product:

Remarks: No data available

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates: Remarks: No data available

#### Components:

#### benzyl alcohol:

Toxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): 230 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 770mg/l

Exposure time: 72 h

Test Type: static test

Method: OECD Test Guideline 201

GLP: yes

#### 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 110 mg/l

Exposure time: 96 h

Test Type: semi-static test

Method: Directive 67/548/EEC, Annex V, C.1.

GLP: yes

Toxicity to daphnia and other aquatic invertebrates: EC50 (Daphnia magna (Water flea)): 23 mg/l

Exposure time: 48 h

Test Type: static test

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae : ErC50 (Scenedesmus capricornutum (fresh water algae)): >50 mg/l

Exposure time: 72 h

Test Type: static test

Method: Directive 67/548/EEC, Annex V, C.3.

GLP: yes

Toxicity to daphnia and other aquatic invertebrates

(Chronic toxicity): NOEC: 3 mg/l

Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test

GLP: yes

#### Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 15 mg/l

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. B - SAFETY DATA SHEET - november 2015- n° batch 274-AE rev.4/15

Exposure time: 96 h

Test Type: semi-static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other  
aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 80 mg/l

Exposure time: 48 h

Test Type: static test

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): 0,32 mg/l

Exposure time: 72 h

Test Type: static test

Method: OECD Test Guideline 201

GLP: yes

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

#### Components:

##### 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Biodegradability : Test Type: aerobic

Result: Not readily biodegradable.

Method: Directive 67/548/EEC Annex V, C.4.A.

GLP: yes

##### Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-:

Biodegradability : Test Type: aerobic

Result: Not readily biodegradable.

Method: OECD Test Guideline 301B

GLP: yes

##### trimethylhexane-1,6-diamine:

Biodegradability : Test Type: aerobic

Result: Not readily biodegradable.

Method: Directive 67/548/EEC Annex V, C.4.A.

GLP: yes

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: No data available

#### Components:

##### 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Partition coefficient: noctanol/water: log Pow: 0,99

Method: OECD Test Guideline 107

GLP: yes

##### Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)-:

Partition coefficient: noctanol/water

: log Pow: 1,34 (25 °C)

Method: OECD Test Guideline 117

GLP: yes

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



C-SYSTEMS 10 10 UV PROTECTION comp. B - SAFETY DATA SHEET - november 2015- n° batch 274-AE rev.4/15

Additional ecological information: Remarks: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : In accordance with local and national regulations.

Container hazardous when empty.

Do not dispose of with domestic refuse.

Do not mix waste streams during collection.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

### SECTION 14: Transport information

#### 14.1 UN number

ADR/RID : UN 2735

IMDG : UN 2735

IATA : UN 2735

#### 14.2 UN proper shipping name

ADR/RID : AMINES, LIQUID, CORROSIVE, N.O.S.  
(octahydro-4,7-methano-1H-indenedimethylamine)

IMDG : AMINES, LIQUID, CORROSIVE, N.O.S.  
(octahydro-4,7-methano-1H-indenedimethylamine)

IATA : Amines, liquid, corrosive, n.o.s.  
(octahydro-4,7-methano-1H-indenedimethylamine)

#### 14.3 Transport hazard class(es)

ADR/RID : 8

IMDG : 8

IATA : 8

#### 14.4 Packing group

##### ADR/RID

Packing group : III

Classification Code : C7

Hazard Identification Number : 80

Labels : 8

##### IMDG

Packing group : III

Labels : 8

EmS Code : F-A, S-B

##### IATA

Packing instruction (cargo aircraft): 856

Packing instruction (passenger aircraft): 852

Packing group : III

Labels : 8

#### 14.5 Environmental hazards

##### ADR/RID

Environmentally hazardous : no

##### IMDG

Marine pollutant : no

#### 14.6 Special precautions for user

Not applicable

#### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

## CECCHI GUSTAVO & C.

Via M. Coppino 253 - 55049 Viareggio (Lu) ITALY  
tel. +39 0584 383694 fax +39 0584 395182  
www.cecchi.it info@cecchi.it



**C-SYSTEMS 10 10 UV PROTECTION comp. B** - SAFETY DATA SHEET - november 2015- n° batch 274-AE rev.4/15

preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). :

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation : Not applicable (Annex XIV)

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major accident hazards involving dangerous substances

Not applicable

### 15.2 Chemical Safety Assessment

Not applicable

## SECTION 16: Other information

### Full text of R-Phrases

R20/22 : Harmful by inhalation and if swallowed.

R21/22 : Harmful in contact with skin and if swallowed.

R22 : Harmful if swallowed.

R34 : Causes burns.

R41 : Risk of serious damage to eyes.

R43 : May cause sensitisation by skin contact.

R52 : Harmful to aquatic organisms.

R52/53 : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R53 : May cause long-term adverse effects in the aquatic environment.

### Full text of H-Statements

H302 : Harmful if swallowed.

H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H317 : May cause an allergic skin reaction.

H318 : Causes serious eye damage.

H332 : Harmful if inhaled.

H411 : Toxic to aquatic life with long lasting effects.

H412 : Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Chronic aquatic toxicity

Eye Dam. : Serious eye damage

Skin Corr. : Skin corrosion

Skin Sens. : Skin sensitisation

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.